



Portable Brix Meter

Check-Brix

RA-250WE



Check Brix within 2 seconds!

Easy to clean

Portable

Easy to read - no graduations!

*For measurements of
sweetness of fruits, vegetables,
drinks and food*

- | | | | | | |
|---|---|--|---|---|---|
| 1-2 Drops

Sample | Quick Meas.

2 Sec. | Waterproof
 | Backlight

LCD with backlight | 30,000 Times

Meas. | Anywhere

Outdoor or Indoor?
It doesn't matter |
| Accurate meas.
with 0.1mL sample | Quick meas. within
2 seconds | Protected against
water jets | LCD with backlight | Long battery life | Outdoor or Indoor?
It doesn't matter |

KYOTO ELECTRONICS

Typical sample and Common Brix%

Category	Samples	0	10	20	30	40
Fruit	Oranges		10	15		
	Pears		10	15		
	Tomatoes	5	10	15		
	Apples		10	15		
	Melons		10	15		
	Strawberries		10	15		
	Peaches		10	15		
	Grapes		10	15	25	
	Water melons		10	15		
	Cherries		10	15		
	Fruit juice	Fruit juices		10	15	
Soft drink	Nectars		10	15		
	Carbonated beverages		10	15		
	Tomato juices	5	10	15		
Tomato processed food	Tomato puree		10	15		
	Tomato ketchup		10	15	30	40
	Lactic acid beverages		10	15		
Dairy goods	Milk		10	15		
	Coffee		10	15		
Seasoning	Soy source		10	15		
	Worcestershire sauce		10	15	30	40
Others	Canned fruit		10	15		

Features

- Sugar content (Brix%) is digitally displayed
- Wide measuring range (0 - 90 Brix%)
- High resolution (0.1 Brix%)
- Temperature Compensation Function
- Easy-operation - just apply sample
- High-performance at a Low price
- Light-weight and compact handheld size
- Easy-to-read LCD with backlight
- Battery operated
- Reliable water proof structure (IP 65)
- Automatic power off



Accurate measurement with a small volume Digital display with the touch of a button

Specifications

Resolution	0.1Brix%
Weight	Approx. 100g (Excluding dry cells)
Dust/Water proof class	P 65 (Dust-tight and protected against water jets)
Precision	±0.2Brix%
Measuring range	0 ~ 90 Brix%
Temperature range	10°C ~ 75°C
Temperature compensation	Built-in
Display	Brix% (With backlight)
Power source	Two AAA dry cells (Alkaline)
Battery life	30,000 measurements (Alkaline cells w/o backlight)
Dimension	43(W) x 26(D) x 170(H) mm



KYOTO ELECTRONICS
MANUFACTURING CO., LTD.

www.kyoto-kem.com



Global Temperature Monitoring Pty Ltd
Tel: (03) 9597 9441
Fax: (03) 9578 7403
Email: enquiries@globaltemp.com.au
Web: www.globaltemp.com.au